# SAART CUM TOTALIZER (MODEL BC-DO)

**SMART** D O SENSOR BAG COUNTER CUM TOTALIZER UNIT is a instrument used for the exact counting of bags, it has a DIFFUSED OPTIC SENSOR fitted on the spiral chute/conveyer or loader of the loading unit

The **SMART** D O BAG COUNTER CUM TOTALIZER UNIT is designed for display of number of bags loaded in the truck or wagon by respective loaders, with programmable counters to generate predefined signals after the counter figure is attained, non ohmic contact output is available for connecting external control devices.



The instrument is Microcontroller based, SWITCH MODE POWER SUPPLY UNIT (SMPS), KEYPAD for programming & counter setting & resetting, seven segment display unit for displaying running COUNT, TOTALISER, SET/PRESET COUNT/TRUCK / WAGON NO. Use of Diffused Optical sensors gives good results, longer life in dusty (CEMENT INDUSTRY) and rough industrial atmosphere.

The unit comes with 3 display:-

- a) Four SEVEN SEGMENT display of 4" showing running COUNTER readings from 0-9999.
- b) Seven SEVEN SEGMENT display of 2.3" showing TOTALIZER / TRUCK / WAGON NO from A-Z, 0-9999999.
- c) Four SEVEN SEGMENT display of 1" showing SET/RESET counts while programming

All the displays are visible from long distance, when the reading reaches or exceeds the predefined count non-ohmic contact output is available for connecting external control devices like alarm, power down, count saving, computer interface, etc.

#### Features:

- Precise counting, high speed, durable & Intelligent to identify continuous bags
- Applicable for single bag counting, continuous bag counting and batch counting.
- Operating on 110-220 V AC SMPS based power supply unit.
- Diffused Optical Sensor
- Pre alarm (last 10 counts to go)
- External ACCESSORY relay contacts
- Power down count saving
- 4 digit seven segment 4 x 4" count display.
- 7 digit seven segment 7 x 2.3" totaliser / Truck/ Wagon No display.
- 4 digit seven segment 4 x 1" set / preset count display.
- Programming keypad with A to Z, 0 to 9, counter reset, totaliser reset & enter keys
- Computer connectivity with operating software; -windows based (optional)
- Weatherproof design for dusty and rough industrial atmospheres.
- Elegant in appearance, rugged & firm in construction.
- Batch counting: available for setting and displaying the number of single bags (0-9999); when the number reaches the set value, a predefined signal can be generated to activate alarm or a signal can be provided for switching the control signals to stop the conveyer/loader (designed as per requirement).
- On reaching the set count value, counter can be reset automatically or manually.

#### TECHNICAL SPECIFICATIONS

### BAG COUNTER & DISPLAY UNIT (MODEL BC-DO):-

#### **Electrical performance: -**

Power Source 110 volts -220 V AC.

Power Supply SMPS .
Power consumption 3 Watts.
Count input mode Sensing Head

Working model Accumulative counting (0-9999)

Display COUNTER (0-9999)

TOTALIZER (0-9999999)
TRUCK / WAGON NO
SET/RESET(0-9999)

Programming Keypad(4 X 3) 0-9, A-Z

CR (counter reset)
TR (totaliser reset)
(enter)

Reset mode manual/automatic reset.

Output contact normally open and closed.

**Environmental: -**

Temperature 0 to +60 C.

Humidity 0 to 95% Rh non-condensing.

Enclosure Dust proof type.

Mechanical: -

Body 18 SWG steel.
Dimension 570 X 300 X 120
Surface Finish Powder coated.

Net weight 2.8 kgs.

Standard mounting WALL MOUNTING

## **CONCEPTS TO INNOVATIONS**

# VOIZLINK

FF 78 RAJAT ARCADE, MIDC T-POINT,

AMRAWATI ROAD, WADI,

NAGPUR -440023.MAHARASHTRA ,INDIA.

PHONE:-+917104-321913, +917104-224381

Fax: +917104-224381.

Cell: - +9198226 95746, +919145427003, +919822941190. Website:- www.voizlink.in.E-mail: - info@voizlink.in.